

Almen Strip Specifications

Grade	SPECIFICATION		LENGTH			WIDTH			THICKNESS			FLATNESS	HARDNESS
C-1S 970046.5	SAE AMS 2432 B	inch	<u>3.008</u> 2.985	2.997	±0.012	<u>0.750</u> 0.745	0.748	±0.0025	<u>0.0944</u> 0.0934	0.0939	±0.0005	±0.0005	HRc 45-48
		mm	<u>76.403</u> 75.819	76.111	±0.292	<u>19.050</u> 18.923	18.987	±0.064	<u>2.398</u> 2.372	2.385	±0.013	±0.013	
C-1 970046.1	SAE J442	inch	<u>3.008</u> 2.985	2.997	±0.012	<u>0.750</u> 0.745	0.7475	±0.0025	<u>0.0949</u> 0.0929	0.0939	±0.0010	±0.0010	HRc 44-50
	SAE AMS 2430 L	mm	<u>76.403</u> 75.819	76.111	±0.292	<u>19.050</u> 18.923	(18.99)	±0.064	<u>2.410</u> 2.360	2.385	±0.025	±0.025	
C-2 970046.2	MIL-S-13165C	inch	<u>3.008</u> 2.985	2.997	±0.012	<u>0.750</u> 0.745	0.7475	±0.0025	<u>0.0948</u> 0.0928	0.0938	±0.0010	±0.0015	HRc 44-50
	AMS-S-13165	mm	<u>76.403</u> 75.819	76.111	±0.292	<u>19.050</u> 18.923	(18.99)	±0.064	<u>2.407</u> 2.357	2.383	±0.025	±0.038	
C-3 Bulk 970046.2	MIL-S-13165C	inch	<u>3.008</u> 2.985	2.997	±0.012	<u>0.750</u> 0.745	0.7475	±0.0025	<u>0.0948</u> 0.0928	0.0938	±0.0010	±0.0015	HRc 44-50
	AMS-S-13165	mm	<u>76.403</u> 75.819	76.111	±0.292	<u>19.050</u> 18.923	(18.99)	±0.064	<u>2.407</u> 2.357	2.383	±0.025	±0.038	

Packaging options:		total
pack	25 pieces per pack	25 pieces
carton	20 packs per carton	500 pieces
half carton	10 packs	250 pieces
box	500 pieces per box	500 pieces